

# Lanolin Based Arterial Fluid with Entrone and AD-P

ADIGLO is a formaldehyde arterial fluid which contains Entrone for achieving penetration to the point of complete saturation and AD-P for control of formaldehyde action to obtain better diffusion and improvement of cosmetic effect. In addition, ADIGLO contains ultra-fine lanolins and cosmetic oils to prevent dehydration and produce a natural look and texture to tissues. ADIGLO is a general purpose arterial fluid suitable for use in all normal cases. ADIGLO is not recommended for use in advanced decomposition or edematous cases.

		ADIO	<b>GLO</b> <sup>B</sup>	DI-SAN⁴	<b>HUMITONE<sup>5</sup></b>
PH-A <sup>1</sup>	DI-SAN <sup>2</sup>	MODERATE FIRMNESS	DEFINITE <sup>3</sup> FIRMNESS	ADD FOR EXTRA FIRMNESS	ADD TO RESTORE MOISTURE CONTENT
3-4	1-2	10-12	14-16	1-3	4-8
$\rightarrow$ $\rightarrow$ MIX IN THIS ORDER $\rightarrow$ $\rightarrow$					
	OUNCES PER GALLON				

# Notes:

- A A value assigned to all Champion fluids ranking them on the basis of preservative ability using recommended dilutions in normal cases. The Champion Preservative Factor is not index but can equal it in certain fluids. It is derived from the total chemical composition of each fluid and results of extensive field research. The Champion Preservative Factor can be used by the embalmer to predict the reactivity, preservative value and firming action of Champion fluids.
- B Add Champion Coloro Dyes as needed to achieve desired cosmetic effect.
- 1 For proper water conditioning and pH balance to maximize fluid efficiency (if using soft water -reduce amount to 2-3 ozs.)
- 2 For sanitizing action in solution and improved fluid action in all non-glutaraldehyde based fluids.
- 3 These are recommended amounts for normal cases. Additional amounts of fluid will be needed for cases with higher aldehyde demand such as cancer, renal and liver diseases with their complications, institutional cases and other wasting diseases, delayed embalming cases, edema and bodies subjected to extensive drug therapy.
- 4 For increased aldehyde action of fluid with improved rigidity and preservation. (Increases preservative factor of fluid without inducing dehydration or other unwanted effects.)
- 5 For maximum rehydration of tissues. Restores moisture in cases of dehydration or emaciation. Use in last 1 to 1-1/2 gallons of solution with intermittent or restricted drainage.

# BEFORE USING, READ SAFETY DATA SHEET. FOR PROFESSIONAL EMBALMING USE ONLY.



# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012) Date of issue: 11/19/2018 Version: 2.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 1.1. Trade name

: ADIGLO

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture Use of the substance/mixture : Arterial Embalming Fluid : For professional use only

#### Details of the supplier of the safety data sheet 1.3.

THE CHAMPION COMPANY 400 Harrison Street Springfield, Ohio 45505

Telephone No. (937) 324-5681

#### 1.4. **Emergency telephone number**

INFOTRAC: 1-800-535-5053 DOMESTIC or 352-323-3500 INTERNATIONAL

### **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

### **GHS-US classification**

Acute Tox. 4 (Oral)	H302
Acute Tox. 4 (Dermal)	H312
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Carc. 1A	H350
STOT SE 1	H370

Full text of H-phrases: see section 16

### 2.2.

### **GHS-US** labelling

Label elements Hazard pictograms (GHS-US) GHS05 GHS07 GHS08 Signal word (GHS-US) : Danger Hazard statements (GHS-US) : H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H350 - May cause cancer H370 - Causes damage to organs (optic nerve, central nervous system) Precautionary statements (GHS-US) : P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P260 - Do not breathe dust, fume, mist, spray, vapors P261 - Avoid breathing dust, fume, mist, spray, vapors P264 - Wash hands thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only in a well-ventilated area P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear protective clothing, protective gloves, eye protection, face protection P285 - In case of inadequate ventilation wear respiratory protection P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P302+P352 - If on skin: Wash with plenty of water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing 11/19/2018 EN (English)

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

<ul> <li>P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing</li> <li>P307+P311 - If exposed: Call a doctor</li> <li>P308+P313 - If exposed or concerned: Get medical attention</li> <li>P310 - Immediately call a POISON CENTER</li> <li>P312 - Call a doctor if you feel unwell</li> <li>P330 - Rinse mouth</li> <li>P333+P313 - If skin irritation or rash occurs: Get medical attention</li> <li>P362 - Take off contaminated clothing and wash before reuse</li> <li>P363 - Wash contaminated clothing before reuse</li> <li>P405 - Store locked up</li> <li>P501 - Dispose of contents and container to comply with applicable local, state, national and international regulation.</li> </ul>

### 2.3. Other hazards

: Spilled material may present a slipping hazard.

other hazards which do not result in classification

2.4. Unknown acute toxicity (GHS-US)

No data available

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substance

## Not applicable

## 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Formaldehyde	(CAS No) 50-00-0	< 15.5	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1A, H350 STOT SE 3, H335
Methyl alcohol	(CAS No) 67-56-1	5 - 11	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 STOT SE 1, H370
Boric acid, disodium salt, pentahydrate	(CAS No) 12179-04-3	<3	Repr. 1B, H360
Boric acid (H3BO3)	(CAS No) 10043-35-3	<1.5	Repr. 1B, H360

# SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a doctor.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep victin warm and rested. Seek medical attention immediately. If breathing stops, give artificial respiration Transfer to hospital rapidly. Immediately call a POISON CENTER.
First-aid measures after skin contact	: Wash immediately with lots of water (15 minutes)/shower. Take off immediately all contaminated clothing. Get medical attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minuter holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and eas to do. Continue rinsing. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. Seek medical attention immediately. Transport to hospital.
First-aid measures after ingestion	: If swallowed, rinse mouth with water (only if the person is conscious). Immediately call a POISON CENTER. Seek medical advice. Give water or milk if the person is fully conscious. Take immediately victim to hospital. Seek medical advice (show the label where possible).
4.2. Most important symptoms and effe	cts, both acute and delayed
Symptoms/injuries	: Causes severe skin burns and eye damage. Causes damage to organs.
Symptoms/injuries after inhalation	: Harmful if inhaled. Danger of serious damage to health by prolonged exposure through inhalation May cause cancer by inhalation. Difficulty in breathing. Causes damage to liver through prolonger or repeated exposure if inhaled. Depression of the central nervous system, headaches, dizziness drowsiness, loss of coordination. Death in extreme cases.
11/19/2018	EN (English) 2/10

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Symptoms/injuries after skin contact	: Harmful in contact with skin. Absorbed through the skin. May cause an allergic skin reaction. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause severe burns.
Symptoms/injuries after eye contact	: Causes serious eye damage. Redness and pain. Impaired vision, watering of eyes, defects in the cornea. Burning sensation. Inflammation. Can cause blindness.
Symptoms/injuries after ingestion	: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. This material contains methanol, which, when ingested, has cards acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death. Ingestion may cause nausea, vomiting and diarrhea. Swallowing can cause severe injury leading to death.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

<b>SECTION 5: Firefighting measur</b>	es
5.1. Extinguishing media	
Suitable extinguishing media	: Alcohol resistant foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.
5.2. Special hazards arising from the	e substance or mixture
No additional information available	
5.3. Advice for firefighters	
Firefighting instructions	<ul> <li>Prevent runoff from entering drains, sewers or waterways. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.</li> </ul>
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection. Wea a self contained breathing apparatus.
Other information	: Combustible liquid. Heat may build pressure, rupturing closed containers, spreading fire an increasing risk of burns and injuries. Use water spray to cool unopened containers. Alcohols bur with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must b exercised in fighting alcohol fires. Vapors are heavier than air and may travel considerable distanc to an ignition source and flash back to source of vapors. Move undamaged containers fror immediate hazard area if it can be done safely. On burning: release of carbon monoxide - carbo dioxide. unburned hydrocarbons. Formaldehyde.
SECTION 6: Accidental release r	neasures
6.1. Personal precautions, protectiv	ve equipment and emergency procedures
General measures	: Stop leak if safe to do so. Avoid breathing dust, fume, mist, spray, vapors. Avoid contact with skin eyes and clothing. Eliminate all ignition sources if safe to do so.
6.1.1. For non-emergency personnel	
Protective equipment	: Wear suitable protective clothing. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	: Avoid breathing dust, fume, mist, spray, vapors. Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.
6.2. Environmental precautions	

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

6.3.	Methods and material for containm	nent and cleaning up
Metho	ds for cleaning up	Keep upwind of the spilled material and isolate exposure . Wear proper protective equipment. Do NOT touch spilled material. Cleanup personnel must be trained in the safe handling of this product. If possible ventilate area by means of non-sparking, grounded ventilation system. Spills may be absorbed on non-reactive absorbents such as vermiculite. Place cells into individual plastic bags and then place into appropriate containers and close tightly for disposal. Ensure that cleanup procedures do not expose spilled material to any moisture. Immediately transport closed containers outside. Contain large spillage with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Gather the product and place it in a spare container that has been suitably labelled. Store away from other materials. Ensure all national/local regulations are observed. Consult the appropriate authorities about waste disposal. Small spills may be flushed to a sanitary sewer with copious amounts of water, if in accordance with local, state or national legislation. Eliminate all sources of ignition, avoid sparks, flames and do not smoke in risk area.

#### 6.4. **Reference to other sections**

See Heading 8. Exposure controls and personal protection.

<b>SECTION 7: Handling and storage</b>			
7.1. Precautions for safe handling			
Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Work in a well-ventilated area. Avoid breathing dust, fume, mist, spray, vapors. Keep away from clothing as well as other incompatible materials. Avoid contact with skin, eyes and clothing. Provide good ventilation in process area to prevent formation of vapor. Keep away from heat, sparks, open flames, hot surfaces No smoking.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practices. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.		
7.2. Conditions for safe storage, includ	ling any incompatibilities		
Technical measures	: A washing facility for eye and skin cleaning purposes should be present. Ensure adequate ventilation. Comply with applicable regulations.		
Storage conditions	<ul> <li>Protect containers against physical damage. Keep only in the original container in a cool, well ventilated place. Store away from direct sunlight or other heat sources. Keep container tightly closed.</li> </ul>		
Incompatible materials	: Strong acids, bases. Oxidizing agents.		
Heat and ignition sources : Store away from direct sunlight or other heat sources.			
7.3. Specific end use(s)			
No additional information qualitable			

No additional information available

### **SECTION 8: Exposure controls/personal protection** 8.1. **Control parameters**

Methyl alcohol (67-5	6-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm)	250 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
Formaldehyde (50-00	0-0)		
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm	
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)	
Boric acid, disodium	salt, pentahydrate (12179-04-3)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m³	
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	6 mg/m³	
Boric acid (H3BO3) (	10043-35-3)		
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m <sup>3</sup> (inhalable fraction)	
11/19/2018	EN (English)		4/10

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Boric acid (H3BO3) (10043-35-3)				
USA ACGIH	ACGIH STEL (mg/m³)	6 mg/m <sup>3</sup> (inhalable fraction)		
8.2. Exposure controls		· · · ·		
Appropriate engineering controls	of any potential exposure.	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate ventilation. Monitoring the effectiveness of engineering control is recommended.		
Personal protective equipment	protection/goggles, face protection/goggles, f	: Avoid all unnecessary exposure. Wear protective clothing, protective gloves, eye protection/goggles, face protection. For certain operations, additional Personal Protection Equipment (PPE) may be required.		
Hand protection		ve nitrile gloves. The quality of the protective gloves resistant to s a function of the specific working place concentration and quantity		
Eye protection	: Contact lenses should not be potential eye contact, irritatio	worn. Chemical goggles and face shields are required to prevent n or injury.		
Skin and body protection	: Long sleeved protective cloth	: Long sleeved protective clothing. Overall. Rubber apron, boots. safety foot-wear.		
Respiratory protection	: In case of insufficient ventilat respirator.	: In case of insufficient ventilation. Wear suitable respiratory equipment. Approved organic vapor respirator.		
Environmental exposure controls	: Avoid discharge to the enviro	: Avoid discharge to the environment.		
Other information	: Do not eat, drink or smoke du	: Do not eat, drink or smoke during use.		

# **SECTION 9: Physical and chemical properties**

SECTION 9. Physical and chemical	
9.1. Information on basic physical and c	hemical properties
Physical state	: Liquid
Color	: Pink
Odor	: Pungent odor
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: 1
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 90.5 °C (195 °F)
Flash point	: 93.3 °C (200 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.052 Specific Gravity
Solubility	: Water: completely soluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 6.7 - 72 vol %
9.2. Other information	
VOC content	: 5%
SECTION 10: Stability and reactivity	

#### 10.1. Reactivity

No additional information available

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

#### 10.2. **Chemical stability**

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. **Conditions to avoid**

Direct sunlight. Extremely high or low temperatures. heat, sparks, open flames, hot surfaces. heat sources.

#### 10.5. **Incompatible materials**

Oxidizing agents. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Thermal decomposition generates : Corrosive vapors. Fume. Carbon monoxide. Carbon dioxide. Formaldehyde.

# SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.	
Methyl alcohol (67-56-1)		
LC50 inhalation rat (mg/l)	130.7 mg/l/4h (lit. ECHA)	
ATE US (oral)	100.0000000 mg/kg bodyweight	
ATE US (dermal)	300.0000000 mg/kg bodyweight	
ATE US (vapors)	3.0000000 mg/l/4h	
Formaldehyde (50-00-0)		
LD50 oral rat	500 mg/kg	
LD50 dermal rabbit	270 mg/kg	
LC50 inhalation rat (mg/l)	0.578 mg/l/4h	
ATE US (oral)	100.0000000 mg/kg bodyweight	
ATE US (dermal)	270.0000000 mg/kg bodyweight	
ATE US (gases)	700.0000000 ppmv/4h	
ATE US (vapors)	0.57800000 mg/l/4h	
ATE US (dust,mist)	0.57800000 mg/l/4h	
Boric acid, disodium salt, pentahydrate (1217	<sup>'</sup> 9-04-3)	
LD50 oral rat	2403 mg/kg	
ATE US (oral)	2403.0000000 mg/kg bodyweight	
Boric acid (H3BO3) (10043-35-3)		
LD50 oral rat	2660 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 0.16 mg/l/4h	
ATE US (oral)	2660.0000000 mg/kg bodyweight	
Skin corrosion/irritation	: Causes severe skin burns and eye damage.	
Serious eye damage/irritation	: Causes serious eye damage.	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
	: Not classified	
	Based on available data, the classification criteria are not met.	
Carcinogenicity	: May cause cancer.	
Formaldehyde (50-00-0)		
IARC group	1 - Carcinogenic to humans	
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens	
	: Not classified	
, , , , , , , , , , , , , , , , , , ,	: Causes damage to organs (optic nerve, central nervous system).	
specific target organ toxicity (single exposure)	. Causes damage to organs (optic nerve, central nervous system).	
Specific target organ toxicity (repeated	: Not classified	
exposure)	Based on available data, the classification criteria are not met.	
1/19/2018	EN (English)	6/10

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

: Not classified
Based on available data, the classification criteria are not met.
: Harmful if inhaled. Toxic if swallowed. Toxic in contact with skin.
: Harmful if inhaled. Danger of serious damage to health by prolonged exposure through inhalation May cause cancer by inhalation. Difficulty in breathing. Causes damage to liver through prolonger or repeated exposure if inhaled. Depression of the central nervous system, headaches, dizziness drowsiness, loss of coordination. Death in extreme cases.
: Harmful in contact with skin. Absorbed through the skin. May cause an allergic skin reaction Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause severe burns.
: Causes serious eye damage. Redness and pain. Impaired vision, watering of eyes, defects in the cornea. Burning sensation. Inflammation. Can cause blindness.
: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. This material contains methanol, which, when ingested, has cards acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death. Ingestion may cause nausea, vomiting and diarrhea. Swallowing can cause severe injury leading to death.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Mathud alashal (67.56.4)		
Methyl alcohol (67-56-1) LC50 fishes 1	> 12700 mg/l 96 hours	
EC50 Daphnia 1	> 10000 mg/l	
	> 10000 mg/r	
Formaldehyde (50-00-0)		
LC50 fishes 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 fish 2	1510 µg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
Boric acid (H3BO3) (10043-35-3)		
EC50 Daphnia 1	115 - 153 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
2.2. Persistence and degradability		
ADIGLO		
Persistence and degradability	Not established.	
2.3. Bioaccumulative potential		
ADIGLO		
Bioaccumulative potential	Not established.	
Formaldehyde (50-00-0)		
Log Pow	0.35 (at 25 °C)	
Boric acid (H3BO3) (10043-35-3)		
. ,. ,	0	
BCF fish 1	0	

# 12.4. Mobility in soil

No additional information available

12.5. Other adverse effects	
Effect on ozone layer	: No additional information available
Effect on the global warming	: No additional information available
Other information	: Avoid release to the environment.

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste disposal recommendations	: It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Dispose of contents/container to comply with applicable local, national and international regulations. Consult the appropriate authorities about waste disposal. Ensure all national/local regulations are observed. Do not pressurize, cut, weld, braze solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources. Do not re-use empty containers. Dispose in a safe manner in accordance with local/national regulations.	
Ecology - waste materials	: Avoid release to the environment. Hazardous waste due to toxicity.	
SECTION 14: Transport information		
In accordance with DOT		
Transport document description	: UN1760, Corrosive liquids, n.o.s. (Formaldehyde), 8, PGIII, ltd. qty.	
	: 8 - Corrosive	
	8	
Packing group (DOT)	: III - Minor Danger	
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154	
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203	
DOT Packaging Bulk (49 CFR 173.xxx)	: 241	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5L	
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.	
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"	
Additional information		
Other information	: No supplementary information available.	
Transport by sea		
No additional information available		
Air transport		
No additional information available		
SECTION 15: Regulatory information		
15.1. US Federal regulations		
ADIGLO		
RQ (Reportable quantity, section 304 of EPA's L	ist of Lists) : 660 lb	
Methyl alcohol (67-56-1)		
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb	
SARA Section 313 - Emission Reporting	1.0 %	
Formaldehyde (50-00-0)		
Listed on the United States SARA Section 302 Listed on United States SARA Section 313		
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	100 lb	
SARA Section 302 Threshold Planning	500	
Quantity (TPQ)		

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 15.2. International regulations

## CANADA

Formaldehyde (50-00-0)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Boric acid (H3BO3) (10043-35-3)	
Listed on the Canadian DSL (Domestic Sustances List)	

Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	

### **EU-Regulations**

### Formaldehyde (50-00-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP] No additional information available

## Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

## No additional information available

15.2.2. National regulations

## Formaldehyde (50-00-0)

Listed on IARC (International Agency for Research on Cancer) Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Japanese Poisonous and Deleterious Substances Control Law

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed as carcinogen on NTP (National Toxicology Program)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Methyl alcohol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			
Formaldehyde (50-00-0)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

## SECTION 16: Other information

## Other information

: None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H360	May damage fertility or the unborn child
H370	Causes damage to organs

## **HMIS III Rating**

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 2 Moderate Hazard
Physical	: 0 Minimal Hazard

SDS US (GHS HazCom 2012)

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.