

# HI-FORM CPF=35<sup>A</sup>

# Special Purpose Arterial Fluid with Entrone and AD-P

HI-FORM is a formaldehyde arterial fluid suitable for use in extreme situations requiring thorough preservation and definite firmness of tissues with minimum dehydration effects. Difficult cases such as serious diseases, delayed embalming or advanced decomposition respond well to HI-FORM. Special buffers and penetrating agents make it possible to obtain maximum tissue fixation and fluid distribution, with enhanced drainage. HI-FORM is not recommended for normal cases.

PH-A¹	TRI-SAN²	HI-FORM <sup>B</sup> DEFINITE <sup>3</sup> FIRMNESS	TRI-SAN⁴ ADD FOR EXTRA FIRMNESS
3-4	1-2	8-10	1-3
→ → MIX IN THIS ORDER → → OUNCES PER GALLON			

#### **Notes:**

- A A value assigned to all Champion fluids ranking them on the basis of preservative ability using recommended dilutions in normal cases. The Champion Preservative Factor is not index but can equal it in certain fluids. It is derived from the total chemical composition of each fluid and results of extensive field research. The Champion Preservative Factor can be used by the embalmer to predict the reactivity, preservative value and firming action of Champion fluids.
- B Add Champion Coloro Dyes as needed to achieve desired cosmetic effect.
- 1 For proper water conditioning and pH balance to maximize fluid efficiency (if using soft water reduce amount to 2-3 ozs.)
- 2 For sanitizing action in solution and improved fluid action in all non-glutaraldehyde based fluids.
- 3 Embalmer should adjust quantity used according to severity of case and fluid action required. For tissue gas use at maximum rate of 16 oz.
- 4 For increased aldehyde action with improved preservation and sanitation. In cases of tissue gas use at rate of 8 oz. Tri-San per gallon.

BEFORE USING, READ SAFETY DATA SHEET. FOR PROFESSIONAL EMBALMING USE ONLY.



# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 11/19/2018

Version: 2.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : HI-FORM

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Arterial Embalming Fluid
Use of the substance/mixture : For professional use only

#### 1.3. Details of the supplier of the safety data sheet

THE CHAMPION COMPANY 400 Harrison Street Springfield, Ohio 45505

Telephone No. (937) 324-5681

#### 1.4. Emergency telephone number

INFOTRAC: 1-800-535-5053 DOMESTIC or 352-323-3500 INTERNATIONAL

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **GHS-US** classification

Flam. Liq. 4 H227 Acute Tox. 3 (Oral) H301 Acute Tox. 3 (Dermal) H311 Acute Tox. 4 (Inhalation:dust,mist) H332 Skin Corr. 1B H314 Eye Dam. 1 H318 Skin Sens. 1 H317 Carc. 1A H350 STOT SE 3 H335 STOT SE 1 H370

# 2.2. Label elements

#### **GHS-US** labelling

Hazard pictograms (GHS-US)



(\*\*\*)





GHS05

GHS06

GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid

H301+H311 - Toxic if swallowed or in contact with skin H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H350 - May cause cancer

H370 - Causes damage to organs

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking

P260 - Do not breathe dust, fume, mist, spray, vapors P261 - Avoid breathing dust, fume, mist, spray, vapors

P264 - Wash hands thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only in a well-ventilated area

P272 - Contaminated work clothing must not be allowed out of the workplace

P280 - Wear eye protection, protective gloves, protective clothing P301+P310 - If swallowed: Immediately call a POISON CENTER

11/19/2018 EN (English) Page 1

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P302+P352 - If on skin: Wash with plenty of water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P307+P311 - If exposed: Call a doctor

P308+P313 - If exposed or concerned: Get medical attention

P310 - Immediately call a POISON CENTER

P312 - Call a doctor if you feel unwell

P330 - Rinse mouth

P333+P313 - If skin irritation or rash occurs: Get medical attention

P361 - Take off immediately all contaminated clothing

P362 - Take off contaminated clothing and wash before reuse

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use alcohol resistant foam, dry powder, carbon dioxide (CO2) to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents and container to comply with applicable local, state, national and international regulation.

#### 2.3. Other hazards

other hazards which do not result in classification

: Spills of this product present a serious slipping hazard.

#### 2.4. Unknown acute toxicity (GHS-US)

No data available

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Formaldehyde	(CAS No) 50-00-0	< 35	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1A, H350 STOT SE 3, H335
Methyl alcohol	(CAS No) 67-56-1	10 - 30	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 STOT SE 1, H370
Boric acid, disodium salt, pentahydrate	(CAS No) 12179-04-3	<3	Repr. 1B, H360

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Give artificial respiration if necessary. Immediately get medical attention.

First-aid measures after skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical attention.

First-aid measures after eye contact

: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.

11/19/2018 EN (English) 2/9

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

First-aid measures after ingestion

: If swallowed, rinse mouth with water (only if the person is conscious). Call a POISON CENTER. Give water or milk if the person is fully conscious. Never give anything by mouth to a person who is not fully conscious. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Causes damage to organs.

Symptoms/injuries after inhalation

: Harmful if inhaled. May cause respiratory irritation. Inhalation of concentrated vapors may cause serious damage to the lining of the nose, throat, and lungs. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Causes damage to liver through prolonged or repeated exposure if inhaled.

Symptoms/injuries after skin contact

: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction. Causes skin irritation. Redness. Dermatitis.

Symptoms/injuries after eye contact

: Causes serious eye damage. Can cause blindness.

Symptoms/injuries after ingestion

: Toxic if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Ingestion may cause nausea and vomiting. Can cause blindness. Death in extreme cases.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media

: Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard

: Combustible liquid.

Explosion hazard

: May form flammable/explosive vapor-air mixture. Vapors can travel considerable distances to a source of ignition where they can ignite, flash back, or explode. Closed containers exposed to heat from fire may build pressure and explode.

#### 5.3. Advice for firefighters

Firefighting instructions

: Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protective equipment for firefighters

: Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus.

Other information

: Combustible liquid. Explosive vapor/air mixtures may be formed. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Containers may swell and Burst during a fire due to internal pressure caused by heat. Special danger of slipping by leaking and spilling product. Thermal combustion may release carbon monoxide and dioxide. unburned hydrocarbons. Toxic gases and fumes may be released in a fire.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Stop leak if safe to do so. Avoid breathing dust, fume, mist, spray, vapors. Avoid contact with skin, eyes and clothing. Eliminate all ignition sources if safe to do so. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires. Gas or vapor heavier than air.

# 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment

: Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

11/19/2018 EN (English) 3/9

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Keep upwind. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Collect all waste in suitable and labelled containers and dispose according to local legislation. Incinerate, dispose in sanitary landfill - if permitted. Small spills may be flushed to a sanitary sewer with copious amounts of water, if in accordance with local, state or national legislation.

Ensure all national and local regulations are observed. Thoroughly wash the area with water after a spill or leak clean-up. Dispose of waste according to applicable legislation.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

- : Obtain special instructions before use. Avoid contact with skin and eyes. Work in a well-ventilated area. When not in use, keep containers tightly closed. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
- Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practices.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Provide local exhaust or general room ventilation. A washing facility for eye and skin cleaning purposes should be present.

Storage conditions

: Keep out of reach of children. Keep only in the original container in a cool, well-ventilated place away from highly flammable substances. Keep container tightly closed and dry. Store away from direct sunlight or other heat sources.

Incompatible materials

: Strong acids, bases. Oxidizing agents.

#### 7.3. Specific end use(s)

No additional information available

#### SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Boric acid, disodium salt, pentahydrate (12179-04-3)		
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (inhalable fraction)
USA ACGIH	ACGIH STEL (mg/m³)	6 mg/m³ (inhalable fraction)

Formaldehyde (50-00-0)		
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)

Methyl alcohol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

#### 8.2. Exposure controls

Appropriate engineering controls

: Provide local exhaust or general room ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment

: Avoid all unnecessary exposure. Wear protective clothing, protective gloves, eye protection/goggles, face protection. For certain operations, additional Personal Protection Equipment (PPE) may be required.

Hand protection

: Wear impermeable protective nitrile gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Eye protection

: Contact lenses should not be worn. Chemical goggles and face shields are required to prevent potential eye contact, irritation or injury.

Skin and body protection

: Long sleeved protective clothing. Overall. Rubber apron, boots. safety foot-wear.

11/19/2018 EN (English) 4/9

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Respiratory protection : In case of insufficient ventilation. Wear suitable respiratory equipment. Approved organic vapor

respirator.

Other information : Do not eat, drink or smoke during use.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: ClearColor: Red

Odor : Pungent odor
Odor threshold : No data available
pH : No data available

Relative evaporation rate (butyl acetate=1) : 1

Melting point : No data available
Freezing point : No data available
Boiling point : 96 °C (205) °F

Flash point : 72.7 °C (163 °F COC)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available

Relative vapor density at 20 °C : 1

Relative density : No data available

Density : 1.083 Specific Gravity

Solubility : Water: completely soluble

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : 6.7 - 72 vol %

9.2. Other information

VOC content : 21 % ( Percent volatiles with heat)

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Stable at normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agents.

#### 10.6. Hazardous decomposition products

On thermal combustion form: Fume. Carbon monoxide. Carbon dioxide. unburned hydrocarbons. Toxic fumes.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

11/19/2018 EN (English) 5/9

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

cording to the federal final rule of hazard communication		
Acute toxicity	: Toxic if swallowed. Toxic in contact with skin. Harmful if inhaled.	
Boric acid, disodium salt, pentahydrate (12179-04-3)		
LD50 oral rat	2403 mg/kg	
ATE US (oral)	2403.0000000 mg/kg bodyweight	
Formaldehyde (50-00-0)		
LD50 oral rat	600 mg/kg	
LD50 dermal rabbit	270 mg/kg	
LC50 inhalation rat (mg/l)	0.578 mg/l/4h	
ATE US (oral)	100.0000000 mg/kg bodyweight	
ATE US (dermal)	270.0000000 mg/kg bodyweight	
ATE US (gases)	700.00000000 ppmv/4h	
ATE US (vapors)	0.57800000 mg/l/4h	
ATE US (dust,mist)	0.57800000 mg/l/4h	
	,	
Methyl alcohol (67-56-1)  LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)	
ATE US (oral)	100.00000000 mg/kg bodyweight	
ATE US (dermal)	300.0000000 mg/kg bodyweight	
ATE US (vapors)	3.00000000 mg/l/4h	
Skin corrosion/irritation	: Causes severe skin burns and eye damage.	
Serious eye damage/irritation	: Causes serious eye damage.	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	
	(Based on available data, the classification criteria are not met)	
Carcinogenicity	: May cause cancer.	
Formaldehyde (50-00-0)		
IARC group	1 - Carcinogenic to humans	
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens	
Reproductive toxicity	: Not classified	
,	(Based on available data, the classification criteria are not met)	
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. Causes damage to organs.	
opeome target organ toxicity (emigic expectato)	. May ease respirately illitation. Sauces damage to organic.	
Specific target organ toxicity (repeated	: Not classified	
exposure)		
•	(Based on available data, the classification criteria are not met)	
Aspiration hazard	: Not classified	
	(Based on available data, the classification criteria are not met)	
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause respiratory irritation. Inhalation of concentrated vapors may cause serious damage to the lining of the nose, throat, and lungs. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Causes damage to liver through prolonged or repeated exposure if inhaled.	
Symptoms/injuries after skin contact	: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction. Causes skin irritation Redness. Dermatitis.	
Outside the Problem of the manufacture	One and a side of the same of	

# **SECTION 12: Ecological information**

Symptoms/injuries after eye contact

Symptoms/injuries after ingestion

#### 12.1. Toxicity

Formaldehyde (50-00-0)	
LC50 fishes 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1510 μg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

extreme cases.

: Causes serious eye damage. Can cause blindness.

: Toxic if swallowed. May cause burns or irritation of the linings of the mouth, throat, and

gastrointestinal tract. Ingestion may cause nausea and vomiting. Can cause blindness. Death in

11/19/2018 EN (English) 6/9

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Formaldehyde (50-00-0)		
	EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

#### 12.2. Persistence and degradability

HI-FORM	
Persistence and degradability	Not established.

#### 12.3. **Bioaccumulative potential**

HI-FORM	
Bioaccumulative potential	Not established.
Formaldehyde (50-00-0)	
Log Pow	0.35 (at 25 °C)

#### 12.4. **Mobility in soil**

No additional information available

#### 12.5. Other adverse effects

Effect on ozone layer : No additional information available Effect on the global warming : No additional information available Other information : Avoid release to the environment.

# **SECTION 13: Disposal considerations**

# Waste treatment methods

: Dispose in a safe manner in accordance with local and national regulations. Incinerate, dispose Waste disposal recommendations

in sanitary landfill - if permitted. Ensure all national and local regulations are observed.

Additional information : Do not re-use empty containers. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose

containers to flames, sparks, heat, or other potential ignition sources.

Ecology - waste materials : Avoid release to the environment.

# **SECTION 14: Transport information**

In accordance with DOT

Transport document description : UN2209, Formaldehyde, solutions, 8, PGIII, ltd.qty.

Hazard labels (DOT) 8 - Corrosive



Packing group (DOT) : 111 DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger **DOT Vessel Stowage Location** 

**DOT Vessel Stowage Other** : 40 - Stow "clear of living quarters"

#### **Additional information**

Other information : No supplementary information available.

#### Transport by sea

No additional information available

#### Air transport

No additional information available

11/19/2018 7/9 EN (English)

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

# **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

HI-FORM	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	309 lb

Formaldehyde (50-00-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	0.1 %

Methyl alcohol (67-56-1)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 313 - Emission Reporting	1.0 %

#### 15.2. International regulations

#### **CANADA**

Formaldehyde (50-00-0)				
Listed on the Canadian DSL (Domestic Sustance	s List)			
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects			

# **EU-Regulations**

# Formaldehyde (50-00-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

#### 15.2.2. National regulations

# Formaldehyde (50-00-0)

Listed on IARC (International Agency for Research on Cancer)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed as carcinogen on NTP (National Toxicology Program)

Listed on the Canadian IDL (Ingredient Disclosure List)

#### 15.3. US State regulations

Formaldehyde (50-00-0)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

11/19/2018 EN (English) 8/9

# Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Methyl alcohol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			

# **SECTION 16: Other information**

Other information : None.

Full text of H-phrases: see section 16:

xt of H-phrases: see section 16:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H360	May damage fertility or the unborn child
H370	Causes damage to organs

# **HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012)

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.

11/19/2018 EN (English) 9/9